



ENGINE-OIL SUPPLEMENT

AUTOMOTIVE ADDITIVES & LUBRICANTS - #0151

OUTSTANDING FEATURES

- Specially formulated to reduce friction and increase the lubricating power of oil.
- Protects new engines during break-in and start up.
- Dispersants and detergents to help prevent sludge buildup.
- Can be used in all types of internal-combustion engines.

DESCRIPTION

Scientifically formulated to increase performance by reducing friction and wear. MOC® Engine-Oil Supplement contains dispersants and detergents to help prevent sludge buildup. This reduction in friction can protect new engines during break-in and startups. It may be used in all internal combustion engines, including rotary and diesel.

APPLICATION

Add entire contents to crankcase at each oil change and between changes, as needed. Treats 4 to 6 quarts of oil.

SPECIFICATIONS

Test	ASTM Method	Typical Results
Appearance	-	Oil
Color	-	Dark Brown
Odor	-	Petroleum
Density (g/mL)	D4052	0.86
Density, U.S. (lbs/gal), calculated	-	7.18
Viscosity, cSt @ 40°C	D445	25
Viscosity, cSt @ 100°C	D445	5
Boiling Point (°F)	-	>400
Flash Point(°F) (based on components)	-	>248
Viscosity Index	-	129

PACKAGING

Fill: 8 oz.

Case Quantity: 24

Case Weight: 14 lbs.