



HEAVY-DUTY DOT 4 BRAKE FLUID

AUTOMOTIVE ADDITIVES & LUBRICANTS - #0601

OUTSTANDING FEATURES

- Contains special additives and esters for excellent high-temperature protection and moisture resistance.
- Extremely high-boiling point formula Dry ERBP: > 262°C (> 503°F), Wet ERPB: >175°C (>346°F)
- Exceeds DOT specifications for DOT 4 brake fluid (DOT minimum is 446°F).
- Two convenient sizes for use with fluid exchange equipment.
- Product can be mixed with other DOT 3 or DOT 4 products.

DESCRIPTION

A high quality product which meets and exceeds the DOT specifications for DOT 4 brake fluid.

APPLICATION

This product is to be used with a #98000 MOC® Pure Brake™ Brake-Fluid Exchanger. Follow directions in the machine's instruction manual for use of this product.

SPECIFICATIONS

<u>Test</u>	ASTM Method	<u>Typical Results</u>
Appearance	-	Clear & Bright
Color	-	Light Yellow
Odor	-	Mild
Specific Gravity @ 68°F	D4052	1.05 - 1.06
Density, U.S. (lbs/gal) (Calculated)	-	8.80
Viscosity, cSt @ -40°C	D445	1,090
Dry ERBP, °F	SAE J-1704	~500
Wet ERBP, °F	SAE J-1704	~346
pH, 50% in EtOH (50/50)	SAE J1704	7.79
pH, 50% in EtOH (80/20)	FMVSS-116	7.64
water %	ASTM E203	<0.24

PACKAGING

<u>Fill:</u> 32 oz.	<u>Case Quantity:</u> 12 Bottles	<u>Case Weight:</u> 29.6 lbs.
<u>Fill:</u> 53 oz.	<u>Case Quantity:</u> 4 Bottles	Case Weight: 16.39 lbs.